

Lithofin MN Power-Clean

Description

A special product from the LITHOFIN-Range for marble, natural and engineered stone (MN). Lithofin MN Power-Clean is free of hydrocarbons, low in odour and economical in use. It is a mildly alkaline cleaner, which contains a balanced mixture of cleaning components which guarantee optimal performance.

Properties

Lithofin MN Power-Clean quickly and effortlessly removes grease and oil, all kinds of general and ingrained dirt as well as floor polish residues, old acrylic emulsions, care products, etc.

Technical Data:

Density: approx. 1.0 g/cm³
 Appearance: liquid, yellowish
 Odour: pleasant, unspecific
 pH-Value: approx. 10
 Flash Point: n.a.
 Solubility in Water: complete

Field of Use

- Thoroughly cleaning used or exceptionally dirty surfaces
- Initial cleaning of newly laid surfaces
- Facilitates removing cement residues from polished marble and limestone
- Suitable for indoor and outdoor use.

Surfaces: Suitable for use on polished, finely honed and rough marble and all types of other natural stones, concrete stone, artificial and engineered stone such as quartz composite.

Directions for Use

Apply and evenly distribute Lithofin MN Power-Clean diluted up to 1:10 and wipe the surface. In case of stubborn dirt deposits, apply undiluted or diluted up to 1:5 with a brush and distribute. Allow the product to work for approx. 15 minutes; brush occasionally. Do not allow to dry, add water if necessary. Brush again before wiping up. On large areas, use a squeegee to remove the product. Wash the surface thoroughly with clean water. If the result is not satisfying, repeat the process allowing the product to work longer and brushing more vigorously.

Please Note: avoid splashes on sensitive areas such as metal or wood, painted or varnished surfaces, wall paper, etc. Always test the product in an inconspicuous area prior to use.

Coverage: as supplied: approx. 10m² depending on dirt diluted: up to 30m².

Advice: for removing wax layers and the like, we recommend Lithofin WAX-OFF.

For cement residues and rust discolorations on granite, gneiss and similar acid resistant stones, use Lithofin MN Builders' Clean.

Storage

Keep closed, cool and dry. Not above 25°C. Shelf life of up to 3 years.

Environmental Protection

Surfactants are biologically degradable in accordance with EU-regulations. Free of phosphates.

Disposal: diluted product may be added to waste water. Containers are made of environmentally friendly polyethylene (PE). Clean containers can be recycled through collection systems.

Safety

Ingredients: 5 - 15% non-ionic surfactants, scent (geraniol).

Labelling according to EU-Directive 1272/2008(CLP):

Avoid prolonged contact with the skin or wear protective gloves.

ADR 2015: labelling for transport

Unit	Label	Notes on freight papers
a) b)	LQ	none, due to limited quantities
c)	8, UN1719	Caustic alkali liquid n.o.s. (glutamic acid, n,n-diacetic acid, tetrasodium salt), 8, UN 1719, III

Packaging

- a) 500ml bottle with child-proof cap (10 per box)
- b) 1 litre bottle with child-proof cap (10 per box)
- c) 5 litre canister (2 per box)

Please Note: statements concerning environmental and safety issues refer to the product as delivered (concentrated). This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Always test the product in an inconspicuous area. (EN2.16gps/4.15)