

Cleaning - Protecting - Maintaining Quarry tiles unglazed

Unglazed quarry tiles are extremely hard wearing and easy to maintain. However, just rinsing the surface with water from time to time is not enough - only proper treatment will ensure a well-maintained appearance for many years to come.

Overview of the 3 Steps *for more detailed instructions, please refer to Page 2*

1

Initial cleaning of newly installed surfaces *used surfaces: Page 2*

Lithofin KF Cement Residue Remover cleans the surface and leaves it clear of all residues.




Coverage:
1 Ltr./20m²



Dilute product 1:4 with water.




Distribute and allow to work for 5 minutes, then scrub.



Remove the solution from the surface.



Rinse well with plenty of clear water.



Allow to dry.

Please Note: allow grout lines to cure for several days before cleaning. Pre-wet the surface to avoid damage to grout lines.

Necessary equipment: bucket, mop and scrubber, squeegee or wet-and-dry vacuum


2a

Protecting against stains *initial cleaning of used surfaces: Page 2*

Lithofin KF Stain-Stop -invisible- protects against oil and water and simplifies maintenance.



Coverage:
1Ltr./15m²




Pour product into a bucket or basin.




Evenly apply with a brush.



Remove all excess product from the surface within 15 min.



Allow to dry for approx. 45 minutes.



Protect from water for 24 hours.

2b

Enhancing the appearance - indoor use only -

Lithofin KF Tile-Polish enhances the colour and produces an elegant sheen.



Coverage:
1 Ltr./15m²

Necessary equipment: bucket, applicator, brush, sponge, cloth

3

Regular maintenance


Lithofin EASY-CARE maintains tile surfaces.



Add one squirt (20ml) to one bucket of water.



Wipe surface with solution. Do not rinse.



Allow to dry. Do not walk on surface during drying time.

Necessary equipment: bucket, mop

Please follow the detailed instructions on the product labels.

Ref. GB-26000 12.20gps

1 Cleaning and refurbishing used or extremely dirty surfaces

Before treating used surfaces, the stone must be thoroughly cleaned. All deposits and care product residues must be removed from the surface and from the pores.

- **Indoors:** dilute Lithofin KF Intensive Cleaner up to 1:10 with water and apply generously to the surface. Allow to work for 5 to 10 minutes. Scrub well with a scrubbing brush or machine and allow to work for an additional 5 minutes. Add water while continuing to brush and rinse off with plenty of water.
- **Outdoors:** in case of dark spots and stubborn dirt deposits, apply Lithofin MN Outdoor Cleaner with a scrubbing brush and allow to work overnight. Rinse off with plenty of clear water the next day.



Allow the surface to dry out thoroughly for several days before applying the protective treatment.

Other, stubborn dirt

Cement residues, builder's dirt, calcium deposits	Lithofin KF Cement Residue Remover or Lithofin CEMENT-AWAY (external use only)
Tar, wax, varnish, paint, oil, grease	Lithofin WAX-OFF
Stubborn oil stains	Lithofin OIL-EX
Green deposits	Lithofin ALGEX
Dirt deposits, algae growth, mould, etc.	Lithofin KF Mildew-Away or Lithofin MN Outdoor Cleaner

2 Additional information about protective treatments

Impregnators such as Lithofin KF Stain-Stop render the surface water and oil repellent. This protective effect reduces staining and facilitates everyday maintenance. The surface becomes easier to maintain and stays beautiful for many years.

Please Note:

Always test the product in an inconspicuous area. Non-absorbent or wet surfaces cannot be treated.

Use impregnators only on completely dry surfaces. Otherwise, the product will be unable to penetrate into the surface.

3 Additional care

Occasionally use Lithofin KF Intensive Cleaner or Lithofin WEXA on surfaces subjected to heavy wear. Depending on the degree of dirt, add up to one litre to a bucket of cold water. Apply with a scrubbing brush and allow to work for 10 to 20 minutes. Do not allow to dry. Remove with a clean cloth and rinse with clear water. Protective treatments may have to be reapplied after this deep clean.

Please Note:

△ Please follow the detailed instructions on the product labels.

This information should be considered to be informal and non-binding.
The products must be used according to local conditions and materials.
Instructions must be read carefully and followed closely. Always test
the products in an inconspicuous area. (GB12.20gps)

If you require advice or are in any way unsure about these instructions, please call our **Technical Support Line at (01962) 732126.**

Your LITHOFIN-Dealer:

■ The Professional Solution

Distribution in UK and Ireland:

CASDRON Enterprises Ltd. · Alesford, Hampshire SO24 9QF · Phone: +44 (0)1962 732 126 · Fax +44 (0)1962 735 373
Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de www.lithofin.com