

## Lithofin LEV solvent based special remover

### Description

A special product from the LITHOFIN-Range. Fast drying, ready-to-use cleaner with highly effective organic solvents.

### Properties

Lithofin LEV dissolves layers of sealants, wax, oil, grease, tar, bitumen and other organic substances such as fresh paint, lacquer, hardened care product residues etc. These deposits can be wiped off directly - without adding water.

#### Technical Data:

Density: 0.90 g/cm<sup>3</sup>

Appearance: liquid, clear, colourless

Odour: fruity

Flash Point: approx. -4°C (c.C.)

Solubility in Water: none

### Field of Use

For removing dirt deposits from solvent resistant surfaces such as all natural and concrete stones, ceramics, tiles, clinker, concrete screed, etc. Suitable for indoor and outdoor use. Ideally suited for degreasing surfaces.

### Directions for Use

Wet the surface with the undiluted product, distribute evenly and allow to work for max. 5 minutes. Add more product, if it begins to dry during that time. Remove any traces with a dry cloth. On large areas work in sections. Process may have to be repeated in case of stubborn stains.

Please note that the product dries within 5 minutes.

**Attention!** Surface temperature must not exceed 25°C.

Switch off underfloor heating. Do not use on solvent sensitive materials such as rubber, paint, lacquer, asphalt, synthetics, etc. Always test product in an inconspicuous area or on a left over tile to establish suitability.

On larger surfaces we recommend using Lithofin WAX-OFF.

Coverage: ca. 3-5 m<sup>2</sup>/Liter.

### Storage

Closed, cool and dry. Not above 25°C, shelf life of up to 5 years.

### Environmental Protection

The contained surfactants are biodegradable according to regulation (EC) No. 648/2004 (detergents regulation).

Disposal: waste code according to EWC/AVV **07 01 04\***.

**Bottles/canisters are made of environmentally friendly tinplate and can be recycled (see information on label).**

### Safety

Ensure good ventilation during and after use. Do not use in rooms where food is stored.

UFI: NDX0-80TU-Y006-2N4K

Ingredients: hydrocarbons, auxiliary agents.

Labelling according to EU-Directive 1272/2008(CLP):

Symbol GHS 02, 07 Danger

Contains ethylacetate. Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Store locked up. Dispose of contents and container in accordance with local and national regulations.

#### ADR2019: labelling for transport

Unit	Label	Notes on freight papers
a)	LQ	none, due to limited quantities
b)	3, UN1173	UN 1173 Ethylacetat, 3, VG II, (D/E)

### Packaging

- a) 1 litre bottle with child-proof cap (10 per box)
- b) 30 litre canister

Please Note: This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Always test the product in an inconspicuous area. (GB11.15gps/11.15)